SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : PURESSENTIEL PURIFYING AIR SPRAY

Product code : CTG140774/1/05.

1.2. Relevant identified uses of the substance or mixture and uses advised against BIOCIDE

1.3. Details of the supplier of the safety data sheet

Registered company name : Laboratoire PURESSENTIEL®. Address : Avenue Molière144. 1050. Brussels BELGIUM Telephone : +32 (0)2 535 75 76 Mail : reglementaire@puressentiel.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net. Belgium poison center : 070/245.245

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1B (Skin Sens. 1B, H317).

2.2. Label elements

Biocidal mixture (see section 15). Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07 GHS02 Signal Word : DANGER Product identifiers : EC 207-431-5 EUCALYPTOL EC 227-813-5 **D-LIMONENE** EC 201-134-4 LINALOOL EC 310-217-5 NIAOULI OIL EC 201-291-9 ALPHA-PINENE X EC 227-815-6 L-LIMONENE EC 204-872-5 **B-PINENE** EC 283-656-2 SPEARMINT OIL 60% EC 277-143-2 PETITGRAIN PARAGUAY OIL CYPRESS OIL PORTUGUESE EC 283-626-9 EC 201-746-1 **BETA-CARYOPHYLLENE** EC 224-052-0 TRANS-ANETHOLE [(E)-ANETHOLE] EC 236-719-3 **DELTA-3-CARENE** EC 237-926-1 L-MENTHONE EC 202-589-1 EUGENOL EC 203-213-9 CINNAMIC ALDEHYDE

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°1 (07/09/2017) Laboratoire PURESSENTIEL®.

Hazard statements : H225	Highly flammable liquid and vanour
H317	Highly flammable liquid and vapour. May cause an allergic skin reaction.
H319 Precautionary statements - General :	Causes serious eye irritation.
P101 P102 P103 Precautionary statements - Prevention :	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P270	Do no eat, drink or smoke when using this product.
Precautionary statements - Response :	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs : Get medical advice/attention.
P337+P313	If eye irritation persists : Get medical advice/attention.
Precautionary statements - Disposal :	
P501	Dispose of contents/container in accordance with national regulations.
Other information :	Keep away from food, drink and animal feedingstuffs.

PURESSENTIEL PURIFYING AIR SPRAY - CTG140774/1/05

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :			
Identification	(EC) 1272/2008	Note	%
CAS: 64-17-5	GHS07, GHS02	[1]	50 <= x % < 100
EC: 200-578-6	Dgr		
REACH: 01-2119457610-43	Flam. Liq. 2, H225		
	Eye Irrit. 2, H319		
ETHANOL			
CAS: 470-82-6	GHS02, GHS07		$2.5 \le x \% \le 10$
EC: 207-431-5	Wng		
REACH: 01-2119967772-24	Flam. Liq. 3, H226		
	Skin Sens. 1B, H317		
EUCALYPTOL			
HYDROCARBONS	GHS08		$2.5 \le x \% \le 10$
	Dgr		
	Asp. Tox. 1, H304		
CAS: 5989-27-5	GHS08, GHS02, GHS07, GHS09		$2.5 \le x \% < 10$
EC: 227-813-5	Dgr		
REACH: 01-2119529223-47	Asp. Tox. 1, H304		
	Flam. Liq. 3, H226		
D-LIMONENE	Skin Irrit. 2, H315		
	Skin Sens. 1B, H317		
	Aquatic Acute 1, H400		
	MAcute = 1		
	Aquatic Chronic 1, H410		
	M Chronic $= 1$		

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°1 (07/09/2017) Laboratoire PURESSENTIEL®.

CA C 70 70 (011007	
CAS: 78-70-6 EC: 201-134-4	GHS07 War	$1 \le x \% < 2.5$
REACH: 01-2119474016-42	Wng Skin Irrit. 2, H315	
КЕАСП. 01-21194/4010-42	Skin Sens. 1B, H317	
LINALOOL	Eye Irrit. 2, H319	
CAS: 115-95-7	GHS07	1 <= x % < 2.5
EC: 204-116-4	Wng	1 - x / 0 - 2.5
REACH: 01-2119454789-19	Eye Irrit. 2, H319	
REACH. 01-2119454769-19	Skin Irrit. 2, H315	
LINALYL ACETATE	Skiii 1111. 2, 11313	
CAS: 8014-68-4	GHS02, GHS08, GHS07, GHS09	$1 \le x \% \le 2.5$
EC: 310-217-5	Dgr	1 - x / 0 - 2.5
10-217-5	Flam. Liq. 3, H226	
NIAOULI OIL	Asp. Tox. 1, H304	
	Skin Irrit. 2, H315	
	Skin Sens. 1, H317	
	Eye Irrit. 2, H319	
	Aquatic Chronic 2, H411	
CAS: 80-56-8	GHS02, GHS07, GHS08, GHS09	0 <= x % < 1
EC: 201-291-9	Dgr	$0 < -x >_0 < 1$
REACH: 01-2119519223-49		
REACH: 01-2119519225-49	Flam. Liq. 3, H226	
ALDILA DINENE V	Asp. Tox. 1, H304	
ALPHA-PINENE X	Skin Irrit. 2, H315	
	Skin Sens. 1B, H317	
	Aquatic Acute 1, H400	
	M Acute = 1	
	Aquatic Chronic 1, H410	
<u></u>	M Chronic = 1	
CAS: 5989-54-8	GHS08, GHS02, GHS07, GHS09	0 <= x % < 1
EC: 227-815-6	Dgr	
	Asp. Tox. 1, H304	
L-LIMONENE	Flam. Liq. 3, H226	
	Skin Irrit. 2, H315	
	Skin Sens. 1B, H317	
	Aquatic Acute 1, H400	
	M Acute = 1	
	Aquatic Chronic 1, H410	
	M Chronic = 1	
CAS: 127-91-3	GHS08, GHS02, GHS07, GHS09	$0 \le x \% < 1$
EC: 204-872-5	Dgr	
REACH: 01-2119519230-54	Flam. Liq. 3, H226	
	Asp. Tox. 1, H304	
B-PINENE	Skin Irrit. 2, H315	
	Skin Sens. 1B, H317	
	Aquatic Acute 1, H400	
	M Acute = 1	
	Aquatic Chronic 1, H410	
	M Chronic = 1	
CAS: 8008-79-5	GHS08, GHS07, GHS09	0 <= x % < 1
EC: 283-656-2	Dgr	
	Asp. Tox. 1, H304	
SPEARMINT OIL 60%	Skin Irrit. 2, H315	
	Skin Sens. 1, H317	
	Aquatic Chronic 2, H411	
CAS: 8016-44-2	GHS05, GHS07	$0 \le x \% \le 1$
EC: 277-143-2	Dgr	
	Skin Irrit. 2, H315	
PETITGRAIN PARAGUAY OIL	Skin Sens. 1, H317	
	Eye Dam. 1, H318	
	Aquatic Chronic 3, H412	
CAS: 8013-86-3	GHS02, GHS08, GHS07, GHS09	$0 \le x \% < 1$
EC: 283-626-9	Dgr	
	Flam. Liq. 3, H226	
CYPRESS OIL PORTUGUESE	Asp. Tox. 1, H304	
	Skin Irrit. 2, H315	
	Skin Sens. 1, H317	
	Aquatic Chronic 2, H411	
	1 Yuuu Chi Oli 2, 11711	

PURESSENTIEL PURIFYING AIR SPRAY - CTG140774/1/05

- Made under licence of European Label System® MSDS software from InfoDyne - http://www.infodyne.fr -

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°1 (07/09/2017) Laboratoire PURESSENTIEL®.

CAS: 87-44-5	GHS07, GHS08	$0 \le x \% \le 1$
EC: 201-746-1	Dgr	0 <- x /0 < 1
LC. 201-740-1	Asp. Tox. 1, H304	
BETA-CARYOPHYLLENE	Skin Sens. 1B, H317	
CAS: 4180-23-8	GHS07	$0 \le x \% \le 1$
EC: 224-052-0	Wng	0 < -x / 0 < 1
REACH: 01-2119979097-22	Skin Sens. 1B, H317	
KEACH. 01-21199/909/-22	Skill Sells. 1D, H317	
TRANS-ANETHOLE [(E)-ANETHOLE]		
CAS: 13466-78-9	GHS08, GHS02, GHS07	0 <= x % < 1
EC: 236-719-3	Dgr	
REACH: 01-2119520252-55	Asp. Tox. 1, H304	
	Flam. Liq. 3, H226	
DELTA-3-CARENE	Skin Irrit. 2, H315	
	Skin Sens. 1B, H317	
CAS: 14073-97-3	GHS07	0 <= x % < 1
EC: 237-926-1	Wng	
	Skin Irrit. 2, H315	
L-MENTHONE	Skin Sens. 1B, H317	
CAS: 79-92-5	GHS02, GHS07, GHS09	0 <= x % < 1
EC: 201-234-8	Wng	
	Flam. Sol. 2, H228	
CAMPHENE	Eye Irrit. 2, H319	
	Aquatic Acute 1, H400	
	MAcute = 1	
	Aquatic Chronic 1, H410	
	M Chronic = 1	
CAS: 97-53-0	GHS07	0 <= x % < 1
EC: 202-589-1	Wng	
REACH: 01-2119971802-33	Eye Irrit. 2, H319	
	Skin Sens. 1B, H317	
EUGENOL		
CAS: 104-55-2	GHS07	$0 \le x \% < 1$
EC: 203-213-9	Wng	
REACH: 01-2119935242-45	Acute Tox. 4, H312	
	Eye Irrit. 2, H319	
CINNAMIC ALDEHYDE	Skin Irrit. 2, H315	
	Skin Sens. 1A, H317	

PURESSENTIEL PURIFYING AIR SPRAY - CTG140774/1/05

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

- water with AFFF (Aqueous Film Forming Foam) additive

- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

Use some absorbent.

The elimination must be carried out by a registrated salvage professionnal.

6.4. Reference to other sections

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

PNEC :

Occupational exposure limits :

-	- ED984 :2012) :						
CAS	VME-ppm :	VME-mg/1	m3 : VLE-ppm :	VLE-mg/m3	: Notes :	TMP No :	
64-17-5	1000	1900	5000	9500	-	84	
- UK / WEL (W	Vorkplace exposure	imits. EH40	/2005. 2007) :				
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :		
64-17-5	1000 ppm						
	1920 mg/m3						
erived no effec	t level (DNEL) or a	lerived mini	imum effect leve	l (DMEL):			
ETHANOL	(CAS: 64-17-5)						
Final use:			Work	ers.			
Exposure			Dermal				
	health effects:			m systemic effec			
DNEL :			343 mg/	kg body weight/d	lay		
Exposure	method		Inhalatic	n an			
	health effects:			rm local effects.			
DNEL :	nearm encets.			g of substance/m3			
DILL.			1700 1112	5 or substance/III5			
Exposure	e method:		Inhalatic				
	health effects:			m systemic effec	ts.		
DNEL :			950 mg	of substance/m3			
Final use:			Man a	exposed via the e	nvironment		
Exposure			Ingestion		nvii onnient.		
	health effects:		Long term systemic effects.				
DNEL :				g body weight/da			
Exposure	method.		Dermal	contact			
Exposure method: Potential health effects:			rm systemic effec	ets			
DNEL :			/kg body weight/				
F	.1 1		T 1 1 /				
Exposure			Inhalation.				
DNEL :	health effects:		Short term local effects. 950 mg of substance/m3				
DNEL :			950 mg	of substance/m5			
Exposure			Inhalati	on.			
Potential	health effects:			Long term systemic effects.			
DNEL :			114 mg of substance/m3				
	ect concentration (I	YNEC):					
	(CAS: 64-17-5)		0.1				
DUTEO	nental compartment:		Soil.	/1 .			
PNEC :			0.63 mg	укд			
Environm	nental compartment:		Fresh w	ater.			
PNEC :	L		0.96 mg				
Es iss			0				
	nental compartment:		Sea wat				
PNEC :			0.79 mg	5/1			
Environm	nental compartment:		Fresh w	ater sediment.			
PNEC :			3.6 mg/				
			-	-			
	nental compartment:			sediment.			
DNEC	1		2 0 mg/				

Marine sediment. 2.9 mg/kg

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :	
Physical state :	Fluid liquid.
Important health, safety and environmental information	
pH :	Not relevant.
Boiling point/boiling range :	78 °C.
Flash Point :	16.00 °C.
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).
Density :	< 1
Water solubility :	Dilutable.
Viscosity:	v < 7 mm2/s (40°C)
Melting point/melting range :	Not relevant.
Self-ignition temperature :	370 °C.
Decomposition point/decomposition range :	370 °C.
9.2. Other information	

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity :	
CINNAMIC ALDEHYDE (CAS: 10) Oral route :	4-55-2) LD50 = 2500 mg/kg
EUGENOL (CAS: 97-53-0) Oral route :	LD50 = 2300 mg/kg
DELTA-3-CARENE (CAS: 13466-78 Oral route :	8-9) LD50 = 4800 mg/kg
TRANS-ANETHOLE [(E)-ANETHO Oral route :	DLE] (CAS: 4180-23-8) LD50 = 3000 mg/kg
ALPHA-PINENE X (CAS: 80-56-8) Oral route :	LD50 = 3500 mg/kg
NIAOULI OIL (CAS: 8014-68-4) Oral route :	LD50 = 3200 mg/kg
LINALOOL (CAS: 78-70-6) Oral route :	LD50 = 2790 mg/kg
EUCALYPTOL (CAS: 470-82-6) Oral route :	LD50 = 2480 mg/kg
Serious damage to eyes/eye irritation : ETHANOL (CAS: 64-17-5) Causes serious eye irritation. Corneal haze :	$1 \le $ Average score < 2 and effects to

 $1 \le$ Average score ≤ 2 and effects totally reversible within 21 days of observation

 $Conjunctival redness: 2 \le Average score \le 2.5 and effects totally reversible within 21 days of observation$

11.1.2. Mixture

No toxicological data available for the mixture.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 97-53-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans. CAS 5989-27-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans. CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

Mixtures : no aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

1993

14.2. UN proper shipping name

UN1993=FLAMMABLE LIQUID, N.O.S. (ethanol)

14.3. Transport hazard class(es)

- Classification :



14.4. Packing group

П

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	1 L	274 601 640D	E2	2	D/E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	3	-	II	1 L	F-E,S-E	274	E2			
						·				
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	II	353	5 L	364	60 L	A3	E2	
	3	-	II	Y341	1 L	-	-	A3	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

- Labelling for biocidal products (Regulation 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC) :

Name	CAS	%	Product-type
ETHANOL	64-17-5	665.00 g/kg	02

Product-type 2 : Disinfectants and algaecides not intended for direct application to humans or animals.

15.2. Chemical safety assessment

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.